



## Шаровые краны ELGEF Plus

- Полиэтилен 100 SDR11 (ISO S5) - от d20 до d225
- Давление для газа 10 бар / воды 16 бар
- d20 - d110 соответствуют DVGW GW336 / DVGW VP302 / DVGW W364
- Клапаны от d160 до d225 поставляются с опорной плитой и ремнями
- d1 = диаметр отверстия
- Для определения границ применения по давлению следует пользоваться действующей нормативно-разрешительной документацией
- \* В соответствии с ANSI B16.40

| d<br>(mm) | Код         | Вес<br>(kg) | d1<br>(mm) | L1<br>(mm) | H<br>(mm) | H1<br>(mm) | t<br>(mm) |     |
|-----------|-------------|-------------|------------|------------|-----------|------------|-----------|-----|
| 20        | 193 103 206 | 0,487       | 23         | 264        | 134       | 96         | 72        |     |
| 25        | 193 103 207 | 0,490       | 23         | 264        | 134       | 96         | 72        |     |
| 32        | 193 103 208 | 0,506       | 23         | 274        | 134       | 96         | 76        |     |
| 40        | 193 103 209 | 0,616       | 30         | 301        | 142       | 100        | 85        |     |
| 50        | 193 103 210 | 0,829       | 38         | 327        | 156       | 107        | 92        |     |
| 63        | 193 103 211 | 1,174       | 48         | 350        | 173       | 114        | 101       |     |
| 75        | 193 103 212 | 1,434       | 48         | 376        | 173       | 114        | 114       |     |
| 90        | 193 103 213 | 2,918       | 68         | 439        | 240       | 158        | 128       |     |
| 110       | 193 103 214 | 4,416       | 83         | 497        | 267       | 171        | 148       |     |
| 125       | 193 103 040 | 4,220       | 62         | 400        | 280       | 195        | 106       |     |
| 160       | 193 103 042 | 10,541      | 88         | 450        | 360       | 235        | 116       |     |
| 180       | 193 103 043 | 10,524      | 88         | 540        | 360       | 235        | 117       |     |
| 200       | 193 103 044 | 12,023      | 88         | 540        | 360       | 235        | 164       |     |
| *         | 225         | 193 103 045 | 24,400     | 120        | 880       | 470        | 322       | 240 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>